


Furniture Castors Series 540 GW, Wheel PU



max 70 kg -20 °C - +60 °C 52-100 mm



Material

coated in polyurethane, 90±3 Shore A
High quality nylon wheel centre, schwarz

Material Fork

Zinc-die-cast housing - chrome plated
Swivel bearing with combined
plain-ball bearing
Wheel brake - glass fibre reinforced
Wheel axle revited

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

– Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	THREAT MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
540 M8 50 PU	Swivel castor	52x8+8	40	62	M8x15	52	==	22,20
541 M8 50 PU	Swivel castor with wheel brake	52x8+8	40	62	M8x15	69	==	27,36
540 M10 50 PU	Swivel castor	52x8+8	40	62	M10x15	52	==	21,96
541 M10 50 PU	Swivel castor with wheel brake	52x8+8	40	62	M10x15	69	==	27,24
540 M12 50 PU	Swivel castor	52x8+8	40	62	M12x15	52	==	23,04
541 M12 50 PU	Swivel castor with wheel brake	52x8+8	40	62	M12x15	69	==	28,08
540 M10 75 PU	Swivel castor	75x13+13	60	93	M10x15	71	==	45,60
541 M10 75 PU	Swivel castor with wheel brake	75x13+13	60	93	M10x15	88	==	53,88
540 M12 75 PU	Swivel castor	75x13+13	60	93	M12x15	71	==	45,60
541 M12 75 PU	Swivel castor with wheel brake	75x13+13	60	93	M12x15	88	==	53,88
540 M10 100 PU	Swivel castor	100x13+13	70	124	M10x15	93	==	62,40
541 M10 100 PU	Swivel castor with wheel brake	100x13+13	70	124	M10x15	116	==	70,68
540 M12 100 PU	Swivel castor	100x13+13	70	124	M12x15	93	==	62,40
541 M12 100 PU	Swivel castor with wheel brake	100x13+13	70	124	M12x15	116	==	70,68