

Levelling Castor Series HRL, Wheel P



max 100 kg -30 °C - +80 °C 40-40 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

++
floor protective

++
weather proof



Material



Casted high quality nylon wheel

Material Fork

Steel housing - zinc plated
double ball race,
levelling foot reinforced nylon with
NBR rubber pad, Ø 40 mm
axle length: 100 mm

- low overall height
- very good manoeuvrability

Advantages

- ✓ THE LEVELLING CASTOR WITH INTEGRATED, ADJUSTABLE MOUNT PROVIDES PERFECT STABILITY. The change from "ROLLING" to "LEVELLING" can take place to a large extent manually. For the last turn a spanner will be required. In the position "levelling", the housing is free of load and can be turned.
- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ easy to clean
- ✓ high chemical resistance

Applications

- Decoration carts
- Stage equipment

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	THREAT MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
HRL M10 40 P	Levelling Castor	40x15+15	100	65-69	M10x20	60	≡	165,00