

Levelling Castor Series HRX, Wheel G



max 100 kg -30 °C - +80 °C 50-50 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

++
floor protective

++
weather proof



Material



Standard rubber tyre grey
Nylon rim

Material Fork

Stainless steel housing 1.4301
double ball race,
pedal: length 140 mm, width 100 mm
levelling foot with NBR rubber pad,
Ø 40 mm

- low overall height
- very good manoeuvrability

Advantages

- ✓ THE LEVELLING CASTOR WITH INTEGRATED ADJUSTABLE MOUNT PROVIDES PERFECT STABILITY. Rotatable through 360° for comfortable operating from any direction. Can be driven up ramps with a 20° gradient.
- ✓ non-marking - floor protective
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Decoration carts
- Stage equipment

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	THREAT MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
HRX M10 50 G	Levelling Castor	50x18+18	100	77-85	M10x20	80	=	634,56