

Stainless Steel Series QX, Wheel PE



 max 1300 kg  -30 °C - +80 °C  125-200 mm

+++
swivels easily


+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Casted high quality nylon wheel

Material Fork



Finish: Polished stainless steel, swivel fork AISI 304, double ball bearing, very strong integrated Kingpin, wheel axle bolted, adjustable total lock

Advantages

- ✓ for extra heavy loads
- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ easy to clean
- ✓ high chemical resistance

Applications

- Wet environments

 ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
QX 125 PEK	Swivel castor	125x40	1300	177	140x110	105x80	12,5	110		470,64
QXT 125 PEK	Swivel castor with total lock	125x40	1300	177	140x110	105x80	12,5	125		495,84
QXF 125 PEK	Fixed castor	125x40	1300	177	140x110	105x80	12,5			381,96
QX 151 PEK	Swivel castor	150x55	1300	211	140x110	105x80	12,5	130		455,40
QXT 151 PEK	Swivel castor with total lock	150x55	1300	211	140x110	105x80	12,5	130		547,20
QXF 151 PEK	Fixed castor	150x55	1300	211	140x110	105x80	12,5			auf Anfrage
QX 200 PEK	Swivel castor	200x55	1300	250	140x110	105x80	12,5	160		auf Anfrage
QXT 200 PEK	Swivel castor with total lock	200x55	1300	250	140x110	105x80	12,5	160		814,80
QXF 200 PEK	Fixed castor	200x55	1300	250	140x110	105x80	12,5			639,24