

Wheels Series AEL ⚡



 max 500 kg  -20° C - +70° C  80-200 mm



Material

coated in polyurethane, 90±3 Shore A electrically conductive
<10⁴Ω
High quality nylon wheel centre

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Fork-lifts

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
80 AELK 8	Wheel	80x32	130	36	36		8	27,00
100 AELK 8	Wheel	100x25	120	30	30		8	36,72
102 AELK 8	Wheel	100x32	150	36	36		8	40,68
127 AELK 8	Wheel	125x32	160	36	36		8	67,44
125 AELK 20	Wheel	125x46	400	50	50		20	99,24
150 AELK 8	Wheel	150x32	180	36	36		8	77,40
160 AELK 20	Wheel	160x46	450	50	50		20	120,84
200 AELK 20	Wheel	200x50	500	50	50		20	224,04