

Wheels Series RN



 max 480 kg  -20 °C - +70 °C  50-250 mm

++

swivels easily

+++

wear resistant

+++

shock proof

+++

floor protective

+++

weather proof



Material

- Elastic solid rubber tyre, blue, 73±5 Shore A, vulcanised on wheel centre
- High quality nylon wheel centre, black
-

Advantages

- ✓ excellent running performance
- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ good abrasion resistance
- ✓ corrosion resistant
- ✓ non-marking

Applications

- Bins
- Refuse bins
- Trash containers
- Refuse containers

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	BAND THICKNESS MM	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
50 RN-6,4	Wheel	50x22	30	5	27	27		6,4	7,92
63 RN-9,5	Wheel	63x25	50	7	33	33		9,5	16,32
75 RN-12	Wheel	75x35	90	7	40	40		12	16,80
100 RNK 15	Wheel	100x40	150	10	40	38		15	40,32
100 RNB 15	Wheel	100x40	150	10	40	40		15	27,96
100 RNBX 15	Wheel	100x40	150	10	40	40		15	31,08
100 RN-15	Wheel	100x40	150	10	40	40		15	21,60
125 RNK 15	Wheel	125x40	180	12,5	40	38		15	47,64
125 RNB 15	Wheel	125x40	180	12,5	40	40		15	34,44
125 RNBX 15	Wheel	125x40	180	12,5	40	40		15	37,92
125 RN-15	Wheel	125x40	180	12,5	40	40		15	35,88
150 RNK 15	Wheel	150x40	240	12,5	50	48		15	58,92
150 RNB 20	Wheel	150x40	240	12,5	50	50		20	40,44
150 RNBX 20	Wheel	150x40	240	12,5	50	50		20	46,44
150 RN-20	Wheel	150x40	240	12,5	50	50		20	33,48
180 RNK 20	Wheel	180x50	350	20	60	54		20	82,80
180 RNB 20	Wheel	180x50	350	20	60	60		20	74,52
180 RNBX 20	Wheel	180x50	350	20	60	60		20	99,36
200 RNK 20	Wheel	200x50	400	30	60	54		20	78,36
200 RNB 20	Wheel	200x50	400	30	60	60		20	70,68
200 RNBX 20	Wheel	200x50	400	30	60	60		20	96,36
250 RNK 20	Wheel	250x50	480	25	60	54		20	127,44
250 RNB 20	Wheel	250x50	480	25	60	60		20	118,92
250 RNBX 20	Wheel	250x50	480	25	60	60		20	145,44
250 RN-20	Wheel	250x50	480	25	60	60		20	106,32