


# Swivel castor HR 80 P

Levelling Castor Series HR - Wheel P

 -30 °C - +80 °C

+++  
swivels easily

+++  
wear resistant

+++  
shock proof

++  
floor protective

++  
weather proof

## Wheel



high quality nylon wheel

Finish: reinforced pressed steel housing zinc plated,  
hardened double ball bearing, sealed, grease nipple, levelling  
foot reinforced black nylon with NBR-rubber pad



Swivel castor	Wheel-Ø A x width B mm: 80 x 30
Load Capacity kg:	200
Load capacity tested according to EN 12530 and EN 12527	
Overall height H mm:	117-123
Dimension of top plate TP mm:	105x85
Hole spacing HS mm:	80x60
Hole-Ø HD mm:	9
Swivel radius SR mm:	191
Wheel bearing:	Nylon plain bearing

## Advantages

THE LEVELLING CASTOR WITH INTEGRATED, ADJUSTABLE MOUNT PROVIDES PERFECT STABILITY. In the position ‚levelling‘, the housing is free of load and can be turned. The force necessary to service the leavers doesn't depend on the weight of the load.

- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ high chemical resistance

©Copyright 2024 Rollenbau GmbH, [www.rollenbau.at](http://www.rollenbau.at) 03.06.2024

## Applications

- Decoration carts
- Stage equipment