

Wheels Series TLEL



 max 800 kg  -20 °C - +80 °C  80-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

++
floor protective

++
weather proof



Material

Coated in cast polyurethane, 95±3 Shore A
Electrically conductive
Core in die-cast aluminium alloy

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ non-marking
- ✓ good chemical resistance

Applications

- Fork-lifts

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
81 TLELK 12	Wheel	80x30	180	40	40		12	54,00
100 TLELK 15	Wheel	100x30	200	30	30		12	41,40
125 TLELK 15	Wheel	125x30	250	30	30		15	63,96
150 TLELK 20	Wheel	150x40	400	40	40		20	88,68
160 TLELK 20	Wheel	160x50	500	60	60		20	113,40
200 TLELK 20	Wheel	200x50	800	60	60		20	141,96
200 TLELK 25	Wheel	200x50	800	60	60		25	141,96