

Feststeller Serie TLC

Truck Locks Series TLC



Gepresster Stahl verzinkt,
Gummifuß: Ø 80 mm

TLCH 151, 165, 195
Pressed steel zinc plated
Footpads: Ø 80 mm



Gusseisen schwarz lackiert,
Gummifuß: Ø 75 mm

TLCH 200
Cast iron black painted finish
Footpads: Ø 75 mm



Gepresster Stahl verzinkt,
Gummifuß: Ø 80 mm

TLCH 151, 165, 195
Pressed steel zinc plated
Footpads: Ø 80 mm



Gepresster Stahl verzinkt,
Gummifuß: Ø 75 mm

TLCMR/L Lever right or left
Pressed steel zinc plated
Footpads: Ø 75 mm

ZEILE	Bauhöhe ausgefahren Extended height	Bauhöhe eingefahren Retracted height				Typ	Artikelnummer	€
1	151	125	120 x 120	85 x 85 oder 100 x 100	10	3	TLCH 151	
2	165	135	115 x 112	75 x 75 oder 92 x 67	10	1	TLCH 165	
3	195	135	115 x 112	75 x 75 oder 92 x 67	10	1	TLCH 195	
4	200	164	152 x 114	127 x 63,5	12	2	TLCH 200	
5	210	170	120 x 120	85 x 85 oder 100 x 100	10	3	TLCH 210	
6	240	212	115 x 112	75 x 75 oder 92 x 67	10	1	TLCH 240	
7	380	350	165 x 115			4	TLCMR	
8	380	350	165 x 115			4	TLCL	

Feststeller bewirken eine weitgehende Sicherheit beim Feststellen eines Transportgerätes. Durch Betätigen des Fußpedals wird wieder sofortige Beweglichkeit erreicht. Die Kraft, die zur Feststellung nötig ist, ist gering und lastunabhängig, da der Gummifuß durch eine große Hebelwirkung lediglich fest an den Boden gepresst wird und die Rollen dabei nicht vom Boden abgehoben werden.

Truck locks are a device to hold a truck or trolley in a fixed position during loading or unloading. They are designed to enable a quick and easy change between the locked and free movement modes. A step down foot-operated pedal moves a skid resistant rubber pad into friction contact with the floor surface. This is done with a spring loaded over cam mechanism that does not lift the load and keeps the operating force low.

