

Wheels Series AL



max 550 kg -30 °C - +80 °C 80-200 mm

++

swivels easily

++

wear resistant

++

shock proof

++

floor protective

+++

weather proof



Material

Coated in injected polyurethane, 58±3 Shore D
High quality nylon wheel centre

Advantages

- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Fork-lifts

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	BAND THICKNESS MM	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
80 ALBX 12	Wheel	80x24	100	3,5	40	40		12	19,44
80 ALB 12	Wheel	80x25	100	3,5	40	40		12	14,28
80 AL-12	Wheel	80x25	100	3,5	40	40		12	9,96
100 ALBX 15	Wheel	100x30	160	2,5	40	40		15	20,52
100 ALB 15	Wheel	100x30	160	2,5	40	40		15	16,92
100 AL-15	Wheel	100x30	160	2,5	40	40		15	13,32
125 ALBX 15	Wheel	125x30	230	4	40	40		15	27,36
125 ALB 15	Wheel	125x30	230	4	40	40		15	23,04
125 AL-15	Wheel	125x30	230	4	40	40		15	19,80
150 ALBX 20	Wheel	150x40	350	5	50	50		20	41,76
150 ALB 20	Wheel	150x40	350	5	50	50		20	36,36
150 AL-20	Wheel	150x40	350	5	50	50		20	31,32
200 ALK 20	Wheel	200x50	550	4,5	60	54		20	85,80
200 ALBX 20	Wheel	200x50	550	4,5	60	60		20	79,56
200 ALB 20	Wheel	200x50	550	4,5	60	60		20	68,52
200 AL-20	Wheel	200x50	550	4,5	60	60		20	61,68