

Ball Units Series Glastransport G



 max 20 kg 

Material

Ball made of black rubber

L = Left; R = Right
Ball in gray rubber, red polyurethane or nylon available on request
Stems and fittings in stainless steel available on request §§

Advantages

- ✓ smooth running
- ✓ silent in motion
- ✓ good abrasion resistance

L = Left; R = Right

Applications

- Haulage way
- Assembly lines



Dimensions

ARTICLE NUMBER	ARTICEL TYPE	BALL-Ø MM	LOAD CAPACITY KG	B MIN/MAX MM	D MM	E MM	C MM	FINISH	PRICE €
SPGR 35/55	Ball Transfer Unit Glass	35	12	54/71	92	14	55	R	27,96
SPGR 35/75	Ball Transfer Unit Glass	35	12	54/71	87	14	75	R	33,60
SPGL 35/55	Ball Transfer Unit Glass	35	12	54/71	92	14	55	L	29,76
SPGL 35/75	Ball Transfer Unit Glass	35	12	54/71	87	14	75	L	33,60
SPGR 50/100	Ball Transfer Unit Glass	50	20	69/71	107	14	100	R	40,32
SPGL 50/100	Ball Transfer Unit Glass	50	20	69/91	107	14	100	L	40,32