

Extra Heavy Duty Series ED, Wheel TLSBA



max 775 kg -20 °C - +80 °C 125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: cast polyurethane, 85 ± 2 Shore A crowned - soft
Core: Die-cast aluminium alloy

Material Fork



For applications where a super strong and durable caster is required,
one tapered roller and one axial ball bearing,
dust protection ring,
very strong integrated Kingpin,
locked nut, grease nipple, wheel axle bolted,
finish – painted

Advantages

- ✓ crowned soft tread makes it very economic
- ✓ very silent in motion
- ✓ very low rolling resistance
- ✓ very revving
- ✓ high abrasion and tear resistance
- ✓ good chemical resistance

Applications

- Heavy duty dollies
- Trash container trucks
- Machinery moving dollies
- Racks



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
ED 125 TLSBAK	Swivel castor	125x50	450	172	135x110	105x80	11	115		229,44
EDF 125 TLSBAK	Fixed castor	125x50	450	172	135x110	105x80	11			119,88
ED 151 TLSBAK	Swivel castor	150x50	575	202	135x110	105x80	13	142		253,68
EDT 151 TLSBAK	Swivel castor with total lock	150x50	575	202	135x110	105x80	13	150		302,76
EDF 151 TLSBAK	Fixed castor	150x50	575	202	135x110	105x80	13			134,88
ED 200 TLSBAK	Swivel castor	200x50	775	251	135x110	105x80	13	172		313,56
EDT 200 TLSBAK	Swivel castor with total lock	200x50	775	251	135x110	105x80	13	172		333,00
EDF 200 TLSBAK	Fixed castor	200x50	775	251	135x110	105x80	13			161,40