

Extra Heavy Duty Series EDD, Wheel RZ



max 700 kg -30 °C - +80 °C 75-82 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Cast polyurethane coating, 95±3 Shore A

Steel wheel centre

Material Fork



For applications where a super strong and durable caster is required,
one tapered roller and one axial ball bearing,
dust protection ring,
very strong integrated Kingpin,
locked nut, grease nipple, wheel axle bolted,
finish – painted

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ high chemical resistance

Applications

- Heavy duty dollies
- Metal-Technology
- Trash container trucks
- Machinery moving dollies
- Workshops
- Racks
- Carpentry
- Building-Industry



SWIVEL CASTOR



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
EDD 75x62 ZK	Swivel castor	75x62	470	127	135x110	105x80	13	98		261,48
EDDF 75x62 ZK	Fixed castor	75x62	470	127	135x110	105x80	13			126,84
EDD 82x70 ZK	Swivel castor	82x70	700	131	135x110	105x80	13	102		269,40
EDDF 82x70 ZK	Fixed castor	82x70	700	131	135x110	105x80	13			135,00