

Forklift wheels Series P



max 1400 kg -20 °C - +80 °C 50-250 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof



Material

_____ Casted high quality nylon wheel

Advantages

- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ easy to clean
- ✓ high chemical resistance

Applications

- Meat processing vats

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
50 P-8	Wheel	50x19	50	22	22		8	0,84
50 P-10	Wheel	50x19	50	22	22		10	0,84
51 P-8	Wheel	50x30	100	36	36		8	3,36
60 P-12	Wheel	60x30	150	40	40		12	6,84
65 P-12	Wheel	65x30	100	40	40		12	3,12
80 PK 15	Wheel	80x30	150	40	38		15	28,56
80 PBX 15	Wheel	80x30	150	40	40		15	16,92
80 PB 15	Wheel	80x30	150	40	40		15	11,52
80 P-12	Wheel	80x30	150	40	40		12	5,76
100 PK 15	Wheel	100x30	175	40	38		15	31,92
100 PBX 15	Wheel	100x30	175	40	40		15	18,84
100 PB 15	Wheel	100x30	175	40	40		15	13,92
100 P-15	Wheel	100x30	175	40	40		15	7,32
100 PL-15	Wheel	100x35	100	40	40		15	5,88
101 PK 15	Wheel	100x37	450	40	38		15	38,64
101 P-15	Wheel	100x37	450	40	40		15	18,60
125 PK 15	Wheel	125x40	300	50	48		15	42,48
125 PBX 20	Wheel	125x40	300	50	50		20	36,36
125 PB 20	Wheel	125x40	300	50	50		20	22,56
125 PLLB 15	Wheel	125x30	250	40	40		15	16,32
125 PLL-15	Wheel	125x30	250	40	40		15	13,56
125 PLB 15	Wheel	125x40	225	49	49		15	12,72
125 P-20	Wheel	125x40	300	50	50		20	9,84
125 P-15	Wheel	125x40	300	50	50		15	9,84
125 PL-15	Wheel	125x35	225	49	49		15	7,68
126 PK 15	Wheel	125x45	700	50	48		15	47,64
126 P-15	Wheel	125x45	700	50	50		15	28,08
150 PK 20	Wheel	150x40	400	50	44		20	50,64
151 PK 20	Wheel	150x48	900	60	54		20	64,80
150 PBX 20	Wheel	150x40	400	50	50		20	40,32
150 PB 20	Wheel	150x40	400	50	50		20	27,24
150 PL-20	Wheel	150x40	370	50	50		20	11,52
150 PL-15	Wheel	150x40	370	50	50		15	12,96
151 P-20	Wheel	150x50	800	60	60		20	24,12
160 P-20	Wheel	160x40	400	50	50		20	14,64
161 P-20	Wheel	160x40	400	58	58		20	14,16
175 PK 25	Wheel	175x50	500	60	54		25	66,84
175 PBX 25	Wheel	175x50	500	60	60		25	65,28
175 PB 25	Wheel	175x50	500	60	60		25	44,04
175 P-25	Wheel	175x50	500	60	60		25	32,04
200 PLK 20	Wheel	200x50	500	50	54		20	42,48
200 PK 25	Wheel	200x50	800	60	52		25	72,36
201 PK 20	Wheel	200x50	1200	60	56		20	79,56
201 PK 25	Wheel	200x50	1200	60	56		25	82,20

200 PLB 20	Wheel	200x50	500	58	58		20	29,76
200 PB 25	Wheel	200x50	600	60	60		25	50,64
200 PL-20	Wheel	200x40	450	50	50		20	23,04
200 P-20	Wheel	200x50	500	60	60		20	25,56
201 P-20	Wheel	200x50	1000	60	60		20	46,44
201 P-25	Wheel	200x50	1000	60	60		25	46,44
250 PK 25	Wheel	250x60	1400	60	56		25	111,24
250 PB 25	Wheel	250x60	1200	74	74		25	113,76
250 P-25	Wheel	250x60	1200	74	74		25	77,16