


Forklift wheels Series RZ



 max 1050 kg  -20 °C - +80 °C  35-85 mm



Material

Cast polyurethane coating, 95±3 Shore A

Steel wheel centre

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ high chemical resistance

Applications

- Fork-lifts

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
RZ 35x27 K6	Wheel	35x27	100	29	29		6	23,76
RZ 50x40 K15	Wheel	50x40	250	40	40		15	61,20
RZ 70x70 K15	Wheel	70x70	500	70	70		15	61,20
RZ 70x100 K20	Wheel	70x100	650	100	96		20	66,60
RZ 70x100 K25	Wheel	70x100	650	100	92		25	69,72
RZ 75x62 K20	Wheel	75x62	470	62	61,6		20	58,92
RZ 75x62 K25	Wheel	75x62	470	62	57,6		25	61,68
RZ 75x76 K17	Wheel	75x76	600	76	72		17	66,60
RZ 75x95 K20	Wheel	75x95	720	95	95		20	68,16
RZ 75x95 K25	Wheel	75x95	720	95	91		25	70,92
RZ 78x78 K20	Wheel	78x78	750	78	74		20	68,28
RZ 78x78 K25	Wheel	78x78	750	78	74		25	71,16
RZ 80x40 K20	Wheel	80x40	400	40	40		20	64,08
RZ 80x40 K25	Wheel	80x40	400	40	40		25	66,60
RZ 80x50 K20	Wheel	80x50	460	50	50		20	58,92
RZ 80x50 K25	Wheel	80x50	460	50	46		25	61,92
RZ 80x54 K20	Wheel	80x54	500	54	54		20	60,96
RZ 80x54 K25	Wheel	80x54	500	54	51		25	62,64
RZ 80x60 K20	Wheel	80x60	550	60	60		20	64,44
RZ 80x60 K25	Wheel	80x60	550	60	60		25	66,84
RZ 80x70 K20	Wheel	80x70	700	70	70		20	65,28
RZ 80x70 K25	Wheel	80x70	700	70	66		25	68,16
RZ 80x80 K20	Wheel	80x80	800	80	80		20	69,24
RZ 80x80 K25	Wheel	80x80	800	80	76		25	72,00
RZ 80x90 K20	Wheel	80x90	900	90	90		20	75,36
RZ 80x90 K25	Wheel	80x90	900	90	86		25	78,36
RZ 82x51 K25	Wheel	82x51	500	51	51		25	70,32
RZ 82x60 K20	Wheel	82x60	600	60	60		20	64,08
RZ 82x60 K25	Wheel	82x60	600	60	56		25	66,60
RZ 82x70 K20	Wheel	82x70	650	70	66		20	67,08
RZ 82x70 K25	Wheel	82x70	650	70	62		25	69,96
RZ 82x75 K20	Wheel	82x75	750	75	75		20	68,64
RZ 82x75 K25	Wheel	82x75	750	75	71		25	71,88
RZ 82x90 K20	Wheel	82x90	900	90	90		20	76,20
RZ 82x90 K25	Wheel	82x90	900	90	90		25	78,84
RZ 82x100 K20	Wheel	82x100	1000	100	100		20	80,64
RZ 82x100 K25	Wheel	82x100	1000	100	96		25	83,04
RZ 85x40 K25	Wheel	85x40	400	40	36		25	66,60
RZ 85x40 K20	Wheel	85x40	400	40	40		20	63,60
RZ 85x54 K20	Wheel	85x54	550	54	54		20	65,76
RZ 85x54 K25	Wheel	85x54	550	54	54		25	68,28
RZ 85x60 K20	Wheel	85x60	700	60	60		20	68,64
RZ 85x60 K25	Wheel	85x60	600	60	60		25	71,88
RZ 85x70 K20	Wheel	85x70	600	70	70		20	69,96

RZ 85x70 K25	Wheel	85x70	700	70	66		25	72,36
RZ 85x75 K20	Wheel	85x75	750	75	75		20	72,48
RZ 85x75 K25	Wheel	85x75	750	75	71		25	75,36
RZ 85x80 K20	Wheel	85x80	800	80	80		20	74,28
RZ 85x80 K25	Wheel	85x80	800	80	76		25	77,04
RZ 85x90 K20	Wheel	85x90	900	90	90		20	79,56
RZ 85x90 K25	Wheel	85x90	900	90	86		25	82,80
RZ 85x95 K20	Wheel	85x95	950	95	95		20	83,04
RZ 85x95 K25	Wheel	85x95	950	95	91		25	85,80
RZ 85x100 K20	Wheel	85x100	1000	100	93		20	83,40
RZ 85x100 K25	Wheel	85x100	1000	100	89		25	86,52
RZ 85x110 K20	Wheel	85x110	1050	110	103		20	90,12
RZ 85x110 K25	Wheel	85x110	1050	110	99		25	93,12