

Forklift wheels Series TL



max 1000 kg -30 °C - +80 °C 80-250 mm

++

swivels easily

+++

wear resistant

+++

shock proof

++

floor protective

++

weather proof



Material

Tread: cast polyurethane, 95±3 Shore A
Core: De-cast aluminium alloy

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Fork-lifts

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	BAND THICKNESS MM	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
80 TLK 12	Wheel	80x20	150	6	20	10		12	29,64
82 TLK 15	Wheel	80x40	250	7	40	38		15	38,40
82 TLB 15	Wheel	80x40	250	7	40	40		15	35,52
100 TLK 15	Wheel	100x30	200	6,5	40	38		15	49,08
100 TLB 15	Wheel	100x30	200	6,5	40	40		15	34,68
101 TLK 15	Wheel	100x40	280	6,5	40	38		15	52,20
101 TLB 15	Wheel	100x40	280	6,5	40	40		15	43,68
125 TLK 15	Wheel	125x30	250	7,5	40	38		15	52,80
126 TLK 20	Wheel	125x50	350	12,5	60	54		20	84,84
125 TLB 15	Wheel	125x30	250	7,5	40	40		15	38,40
126 TLB 20	Wheel	125x50	350	12,5	60	60		20	65,16
150 TLK 20	Wheel	150x40	400	8	50	48		20	74,28
150 TLB 20	Wheel	150x40	400	8	50	50		20	57,48
160 TLK 20	Wheel	160x50	600	10	60	54		20	93,12
160 TLB 20	Wheel	160x50	600	10	60	60		20	72,24
175 TLK 20	Wheel	175x40	550	9	50	44		20	84,84
175 TLB 20	Wheel	175x40	550	9	50	50		20	68,16
180 TLK 20	Wheel	180x50	700	20	60	54		20	118,56
180 TLB 20	Wheel	180x50	700	20	60	60		20	98,28
200 TLK 20	Wheel	200x50	800	8	60	54		20	112,56
200 TLB 20	Wheel	200x50	800	8	60	60		20	89,16
225 TLK 20	Wheel	225x60	1000	17,5	70	64		20	150,12
225 TLB 20	Wheel	225x60	1000	17,5	70	70		20	142,80
250 TLK 25	Wheel	250x60	1000	11	60	56		25	168,36