

Forklift wheels Series Z



max 3200 kg -30 °C - +80 °C 75-400 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof



Z

Material

Tread: Cast polyurethane, 95±3 Shore A
Wheel centre, Cast-iron - painted

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Fork-lifts

Dimensions

ARTICLE NUMBER	ARTICLE TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	BAND THICKNESS MM	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
75 ZK 12	Wheel	75x29	150	8	39	39		12	45,48
80 ZK 12	Wheel	80x20	150	7	18	10		12	34,68
82 ZK 12	Wheel	82x28	220	11	28	26		12	48,72
82 ZK 15	Wheel	82x28	220	11	28	24		15	48,72
83 ZK 12	Wheel	82x34	270	10	34	32		12	51,72
83 ZK 15	Wheel	82x34	270	10	34	30		15	51,72
100 LZK 15	Wheel	100x30	300	8	30	30		15	50,40
100 LZK 17	Wheel	100x30	300	8	30	28		17	50,40
100 ZK 15	Wheel	100x30	300	8	40	38		15	54,00
100 ZK 17	Wheel	100x30	300	8	40	36		17	54,00
101 ZK 20	Wheel	100x40	300	9	40	40		20	75,36
101 ZK 25	Wheel	100x40	300	9	40	36		25	75,36
102 ZK 17	Wheel	100x50	450	15	50	44		17	68,64
102 ZK 20	Wheel	100x50	450	15	50	44		20	68,64
102 ZK 25	Wheel	100x50	450	15	50	40		25	68,64
125 ZK 15	Wheel	125x30	330	14	40	38		15	61,44
125 ZK 17	Wheel	125x30	330	14	40	36		17	61,44
126 ZK 17	Wheel	125x40	400	12	50	44		17	87,36
126 ZK 20	Wheel	125x40	400	12	50	44		20	87,36
126 ZK 25	Wheel	125x40	400	12	50	40		25	87,36
127 ZK 17	Wheel	125x50	480	10	50	44		17	103,56
127 ZK 20	Wheel	125x50	480	10	50	44		20	103,80
127 ZK 25	Wheel	125x50	480	10	50	40		25	103,80
140 ZK 20	Wheel	140x60	700	12,5	68	54		20	126,12
140 ZK 25	Wheel	140x60	700	12,5	68	54		25	126,12
150 LZK 15	Wheel	150x30	400	9,5	40	38		15	75,36
150 LZK 17	Wheel	150x30	400	9,5	40	36		17	75,36
150 ZK 17	Wheel	150x40	500	9,5	50	48		17	93,48
150 ZK 20	Wheel	150x40	500	9,5	50	48		20	93,48
150 ZK 25	Wheel	150x40	500	9,5	50	46		25	93,48
151 LZK 17	Wheel	150x50	700	9,5	50	44		17	91,92
151 LZK 20	Wheel	150x50	700	9,5	50	44		20	91,92
151 LZK 25	Wheel	150x50	700	9,5	50	40		25	91,92
151 ZK 17	Wheel	150x50	700	9,5	60	54		17	109,44
151 ZK 20	Wheel	150x50	700	9,5	60	54		20	110,28
151 ZK 25	Wheel	150x50	700	9,5	60	50		25	110,28
175 ZK 17	Wheel	175x40	650	10,5	50	44		17	104,40
175 ZK 20	Wheel	175x40	650	10,5	50	44		20	104,40
175 ZK 25	Wheel	175x40	650	10,5	50	40		25	104,40
200 LZK 17	Wheel	200x40	800	12,5	50	44		17	123,48
200 LZK 20	Wheel	200x40	800	12,5	50	44		20	124,32
200 LZK 25	Wheel	200x40	800	12,5	50	40		25	124,32
200 ZK 17	Wheel	200x50	1000	12,5	60	54		17	135,72
200 ZK 20	Wheel	200x50	1000	12,5	60	54		20	136,80

200 ZK 25	Wheel	200x50	1000	12,5	60	56		25	139,44
201 ZK 25	Wheel	200x80	1400	19,5	80	82		25	306,36
201 ZK 30	Wheel	200x80	1400	19,5	80	80		30	307,32
201 ZK 35	Wheel	200x80	1400	19,5	80	76		35	307,32
250 LZK 20	Wheel	250x50	1200	12,5	60	56		20	223,68
250 LZK 25	Wheel	250x50	1200	12,5	60	56		25	223,68
250 ZK 20	Wheel	250x60	1400	13	72,5	71		20	223,68
250 ZK 25	Wheel	250x60	1400	13	72,5	71		25	223,68
251 ZK 25	Wheel	250x80	1800	18	90	90		25	350,88
251 ZK 30	Wheel	250x80	1800	18	90	90		30	350,88
300 ZK 30	Wheel	300x70	2200	13,5	72,5	72		30	372,84
300 ZK 35	Wheel	300x70	2200	13,5	72,5	70		35	372,84
301 ZK 40	Wheel	300x100	2800	25	120	119		40	650,76
400 ZK 40	Wheel	400x100	3200	25	120	120		40	1150,92