

Furniture Castors Series 530 GW, Wheel PEL⚡

max 60 kg -20 °C - +60 °C 52-75 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material

Casted high quality nylon wheel, black
electrically conductive $<10^4 \Omega$

Material Fork

High quality nylon housing - black
Swivel bearing with combined
plain-ball bearing
Wheel brake - glass fibre reinforced
Wheel axle revited

Advantages

- ✓ electrically conductive
- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ easy to clean
- ✓ high chemical resistance

Applications

– Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	THREAT MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
530 M8 50 PEL	Swivel castor	52x8+8	40	62	M8x15	52	==	19,80
531 M8 50 PEL	Swivel castor with wheel brake	52x8+8	40	62	M8x15	69	==	24,00
530 M10 50 PEL	Swivel castor	52x8+8	40	62	M10x15	52	==	18,84
531 M10 50 PEL	Swivel castor with wheel brake	52x8+8	40	62	M10x15	69	==	23,76
530 M12 50 PEL	Swivel castor	52x8+8	40	62	M12x15	71	==	20,52
531 M12 50 PEL	Swivel castor with wheel brake	52x8+8	40	62	M12x15	88	==	24,36
530 M10 75 PEL	Swivel castor	75x13+13	60	93	M10x15	72	==	35,40
531 M10 75 PEL	Swivel castor with wheel brake	75x13+13	60	93	M10x15	88	==	42,48
530 M12 75 PEL	Swivel castor	75x13+13	60	93	M12x15	72	==	35,40
531 M12 75 PEL	Swivel castor with wheel brake	75x13+13	60	93	M12x15	88	==	42,36