

Furniture Castors Series 540 GW, Wheel PUEL ⚡

max 70 kg -20 °C - +60 °C 52-100 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material

coated in polyurethane, 90±3 Shore A
electrically conductive $<10^4 \Omega$
High quality nylon wheel centre

Material Fork

Zinc-die-cast housing - chrome plated
Swivel bearing with combined
plain-ball bearing
Wheel brake - glass fibre reinforced
Wheel axle revited

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	THREAT MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
540 M8 50 PUEL	Swivel castor	52x8+8	40	62	M8x15	52	==	32,88
541 M8 50 PUEL	Swivel castor with wheel brake	52x8+8	40	62	M8x15	69	==	38,16
540 M10 50 PUEL	Swivel castor	52x8+8	40	62	M10x15	52	==	32,64
541 M10 50 PUEL	Swivel castor with wheel brake	52x8+8	40	62	M10x15	69	==	37,92
540 M12 50 PUEL	Swivel castor	52x8+8	40	62	M12x15	52	==	33,48
541 M12 50 PUEL	Swivel castor with wheel brake	52x8+8	40	62	M12x15	69	==	38,40
540 M10 75 PUEL	Swivel castor	75x13+13	60	93	M10x15	71	==	65,28
541 M10 75 PUEL	Swivel castor with wheel brake	75x13+13	60	93	M10x15	88	==	72,48
540 M12 75 PUEL	Swivel castor	75x13+13	60	93	M12x15	71	==	65,28
541 M12 75 PUEL	Swivel castor with wheel brake	75x13+13	60	93	M12x15	88	==	72,12
540 M10 100 PUEL	Swivel castor	100x13+13	70	124	M10x15	93	==	84,36
541 M10 100 PUEL	Swivel castor with wheel brake	100x13+13	70	124	M10x15	116	==	91,92
540 M12 100 PUEL	Swivel castor	100x13+13	70	124	M12x15	93	==	80,40
541 M12 100 PUEL	Swivel castor with wheel brake	100x13+13	70	124	M12x15	116	==	91,92