

Furniture Castors Series 540 ST, Wheel PUEL ⚡

max 70 kg -20 °C - +60 °C 52-100 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material

coated in polyurethane, 90±3 Shore A
electrically conductive <10⁴Ω
High quality nylon wheel centre

Material Fork

Zinc-die-cast housing - chrome plated
Swivel bearing with combined
plain-ball bearing
Wheel brake - glass fibre reinforced
Wheel axle revited

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
540 10x34 50 PUEL	Swivel castor	52x8+8	40	62	10x34	52	==	34,68
541 10x34 50 PUEL	Swivel castor with wheel brake	52x8+8	40	62	10x34	69	==	39,48
540 11x22 50 PUEL	Swivel castor	52x8+8	40	62	11x22	52	==	33,48
541 11x22 50 PUEL	Swivel castor with wheel brake	52x8+8	40	62	11x22	69	==	38,40
540 10x34 75 PUEL	Swivel castor	75x13+13	60	93	10x34	71	==	68,52
541 10x34 75 PUEL	Swivel castor with wheel brake	75x13+13	60	93	10x34	88	==	76,20
540 11x30 75 PUEL	Swivel castor	75x13+13	60	93	11x30	71	==	70,92
541 11x30 75 PUEL	Swivel castor with wheel brake	75x13+13	60	93	11x30	88	==	78,36
540 10x34 100 PUEL	Swivel castor	100x13+13	70	125	10x34	93	==	87,72
541 10x34 100 PUEL	Swivel castor with wheel brake	100x13+13	70	125	10x34	116	==	95,52
540 11x30 100 PUEL	Swivel castor	100x13+13	70	125	11x30	93	==	89,88
541 11x30 100 PUEL	Swivel castor with wheel brake	100x13+13	70	125	11x30	116	==	97,20