

Furniture Castors Series 550 GW, Wheel PUEL ⚡

KG max 100 kg -20 °C - +60 °C 65-125 mm

+++
swivels easily

+++
wear resistant

++
shock proof

++
floor protective

+++
weather proof

Material

coated in polyurethane, 90±3 Shore A
electrically conductive <10⁴Ω
High quality nylon wheel centre

Material Fork

Design-twin wheel castor, (RAL 7004) with Swivel bearing with combined plain-ball bearing, Lock - glass fibre reinforced, Wheel axle revited 1262
resilient PUR-tread, non-marking, wheel-/total lock Design Zentrum Nordrhein-Westfalen Design award winner 2000 Industrie Forum Design Hannover

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Health-Professionals

ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	THREAT MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
550 M10 65 PUEL	Swivel castor	65x14+14	70	79	M10x15	57		38,64
551 M10 65 PUEL	Swivel castor with wheel brake	65x14+14	70	79	M10x15	68		44,28
550 M12 65 PUEL	Swivel castor	65x14+14	70	79	M12x15	57		38,64
551 M12 65 PUEL	Swivel castor with wheel brake	65x14+14	70	79	M12x15	68		44,28
550 M10 75 PUEL	Swivel castor	75x18+18	70	90	M10x15	67		49,68
551 M10 75 PUEL	Swivel castor with total lock	75x18+18	70	90	M10x15	79		66,36
550 M12 75 PUEL	Swivel castor	75x18+18	70	90	M12x15	67		49,68
551 M12 75 PUEL	Swivel castor with total lock	75x18+18	70	90	M12x15	132		66,84
550 M10 100 PUEL	Swivel castor	100x20+20	70	119	M10x15	87		111,60
551 M10 100 PUEL	Swivel castor with total lock	100x20+20	70	119	M10x15	105		123,96
550 M12 100 PUEL	Swivel castor	100x20+20	100	119	M12x15	87		111,60
551 M12 100 PUEL	Swivel castor with total lock	100x20+20	100	119	M12x15	105		123,12
550 M12 125 PUEL	Swivel castor	125x20+20	100	149	M12x25	107		142,08
551 M12 125 PUEL	Swivel castor with total lock	125x20+20	100	149	M12x25	132		159,60