

Guide Rollers Series PAK



 max 490 kg  -20 °C - +70 °C  30-80 mm


swivels easily


wear resistant


shock proof


floor protective


weather proof



Material

High quality nylon wheel, Ball bearing extrusion molded

* Type X: plane tread • Type Y: tread edges rounded • Type Z: crowned tread

Advantages

- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ easy to clean
- ✓ high chemical resistance

Applications

- Haulage way
- Assembly lines
- Mechatronik

Dimensions

ARTICLE NUMBER	ARTICLE TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	HUB WIDTH MM	FIXING LENGTH MM	WHEEL BEARING	BORE DIAMETER MM	PRICE €
30x11 PAK 8	Wheel	30x11	60		7		8	19,20
38x28 PAK 12	Wheel	38x28	80		10		12	20,88
38x38 PAK 12	Wheel	38x38	80		10		12	32,16
40x14 PAK 10	Wheel	40x14	100		8		10	39,48
40x16 PAK 15	Wheel	40x16	120		9		15	38,40
40x18 PAK 10	Wheel	40x18	140		18,5		10	46,56
42x14 PAK 10	Wheel	42x14	110		8		10	34,20
42x14 PAK 12	Wheel	42x14	110		10		12	32,04
42x28 PAK 10	Wheel	42x28	110		8		10	26,16
42x28 PAK 12	Wheel	42x28	110		10		12	20,76
42x38 PAK 12	Wheel	42x38	130		10		12	25,20
44x16 PAK 12	Wheel	44x16	130		8		12	25,20
50x15 PAK 10	Wheel	50x15	140		9		10	21,24
50x15 PAK 12	Wheel	50x15	140		10		12	21,24
50x15 PAK 12 ZZ	Wheel	50x15	140		8		12	19,20
50x18 PAK 12	Wheel	50x18	170		10		12	33,96
50x20 PAK 12	Wheel	50x20	190		10		12	31,32
54x22 PAK 12	Wheel	54x22	230		10		12	29,40
55x25 PAK 15	Wheel	55x25	270		9		15	26,88
60x30 PAK 15	Wheel	60x30	350		13		15	60,00
62x20 PAK 12	Wheel	62x20	240		19,2		12	63,48
65x18 PAK 10	Wheel	65x18	230		9		10	38,40
65x18 PAK 12	Wheel	65x18	230		10		12	38,40
70x35 PAK 20	Wheel	70x35	490		41		20	94,08
80x20 PAK 12	Wheel	80x20	310		10		12	36,48
80x20 PAK 15	Wheel	80x20	310		11		15	34,08
80x20 PAK 17	Wheel	80x20	310		12		17	34,08
80x25 PAK 25	Wheel	80x25	400		12		25	46,56