

Heat Series CDH, Wheel RH



max 100 kg -35 °C - +270 °C 100-100 mm

++

swivels easily

+++

wear resistant

++

shock proof

++

floor protective

+++

weather proof

Material



Heat resistant red running surface made of Teflon
Revised aluminium rim

Material Fork



Finish: electro-zinc plated, double ball bearing – revited, hardened steel balls, dust protection ring for temperatures up to max. 270° C, high melting point grease, wheel axle bolted

Advantages

- ✓ heat- and deep-freeze resistant
- ✓ silent in motion
- ✓ maintenance free
- ✓ very durable

Applications

- Bread racks



SWIVEL CASTOR



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CDH 100 RHX	Swivel castor	100x30	100	128	102x83	80x60	9	88	==	168,36
CDF 100 RHX	Fixed castor	100x30	100	128	102x83	80x60	9		==	160,68