

Heat Series CDH, Wheel HB

 max 230 kg  -20 °C - +120 °C  100-200 mm

 **swivels easily**

 **wear resistant**

 **shock proof**

 **floor protective**

 **weather proof**

Material



Standard rubber tyre black, heat-resistant
Bolted steel rim, zinc-plated

Material Fork



Finish: electro-zinc plated, double ball bearing – revited, hardened steel balls, dust protection ring for temperatures up to max. 270° C, high melting point grease, wheel axle bolted

Advantages

- ✓ heat resistant
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Bread racks

 **ROLLENBAU**



SWIVEL CASTOR



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CDH 100 HB	Swivel castor	100x30	80	128	102x83	80x60	9	88		70,68
CDF 100 HB	Fixed castor	100x30	80	128	102x83	80x60	9			58,92
CSH 125 HB	Swivel castor	125x38	120	160	102x83	80x60	9	113		94,44
CFS 125 HB	Fixed castor	125x38	120	160	102x83	80x60	9			77,04
CSSH 125 HB	Swivel castor	125x38	120	160	135x110	105x80	11	113		98,16
CSSF 125 HB	Fixed castor	125x38	120	160	135x110	105x80	11			81,00
CDH 160 HB	Swivel castor	160x40	180	203	135x110	105x80	11	138		147,00
CDF 160 HB	Fixed castor	160x40	180	203	135x110	105x80	11			125,64
CDH 200 HB	Swivel castor	200x50	230	240	135x110	105x80	11	161		171,00
CDF 200 HB	Fixed castor	200x50	230	240	135x110	105x80	11			142,80