

Heat Series CDH, Wheel FS



max 370 kg -40 °C - +270 °C 80-200 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Wheel made of special thermo resistant compound

Material Fork



Finish: electro-zinc plated, double ball bearing – revited, hardened steel balls, dust protection ring for temperatures up to max. 270° C, high melting point grease, wheel axle bolted

Advantages

Applications

- Bread racks



SWIVEL CASTOR



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
CDH 80 FS	Swivel castor	80x30	150	106	102x83	80x60	9	75	=	33,24
CDF 80 FS	Fixed castor	80x30	150	106	102x83	80x60	9		=	21,24
CDH 100 FS	Swivel castor	100x30	150	128	102x83	80x60	9	88	=	39,00
CDF 100 FS	Fixed castor	100x30	150	128	102x83	80x60	9		=	27,36
CSH 125 FS	Swivel castor	125x38	250	160	102x83	80x60	9	113	=	63,00
CFS 125 FS	Fixed castor	125x38	250	160	102x83	80x60	9		=	46,56
CSSH 125 FS	Swivel castor	125x38	250	160	135x110	105x80	11	113	=	66,60
CSSF 125 FS	Fixed castor	125x38	250	160	135x110	105x80	11		=	51,72
CDH 150 FS	Swivel castor	150x45	300	203	135x110	105x80	11	134	=	96,48
CDF 150 FS	Fixed castor	150x45	300	203	135x110	105x80	11		=	75,36
CDH 200 FS	Swivel castor	200x50	370	240	135x110	105x80	11	161	=	132,96
CDF 200 FS	Fixed castor	200x50	370	240	135x110	105x80	11		=	111,72