

Heat Series XDH, Wheel HB



max 230 kg -20 °C - +120 °C 100-200 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Standard rubber tyre black, heat-resistant
Bolted steel rim, zinc-plated

Material Fork



Finish: Polished stainless steel housing AISI 304, stainless steel balls AISI 420, double ball bearing, revited, dust protection ring up to max. 270° C, high melting point grease, wheel axle bolted

Advantages

- ✓ heat resistant
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Meat processing vats
- Bread racks



SWIVEL CASTOR



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
XDH 100 HBX	Swivel castor	100x30	80	128	102x83	80x60	9	88		147,84
XF 100 HBX	Fixed castor	100x30	80	128	102x83	80x60	9			123,48
XSH 125 HBX	Swivel castor	125x38	120	160	102x83	80x60	9	113		179,04
XFS 125 HBX	Fixed castor	125x38	120	160	102x83	80x60	9			140,04
XSSH 125 HBX	Swivel castor	125x38	120	160	135x110	105x80	11	113		187,80
XFSS 125 HBX	Fixed castor	125x38	120	160	135x110	105x80	11			153,84
XSH 160 HBX	Swivel castor	160x40	180	203	135x110	105x80	11	138		273,00
XFS 160 HBX	Fixed castor	160x40	180	203	135x110	105x80	11			214,68
XDH 200 HBX	Swivel castor	200x50	230	240	135x110	105x80	11	161		320,64
XF 200 HBX	Fixed castor	200x50	230	240	135x110	105x80	11			271,68