

Heavy Duty Series 61, Wheel SU

 max 540 kg  -30 °C - +80 °C  100-150 mm

 **swivels easily**

 **wear resistant**

 **shock proof**

 **floor protective**

 **weather proof**

Material



Tread: Cast polyurethane, 95±3 Shore A
Wheel centre, Cast-iron - painted

Material Fork



Large swivel bearing – for a long service life, zinc plated, specially formed forklegs – high load capacity, wheel axle bolted – locked, wheel brake

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Heavy duty dollies
- Machinery moving dollies
- Scaffolds

 **ROLLENBAU**



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
61-100 SUB	Swivel castor	100x43	300	125	128x102	105x80	11	79		112,56
61BR-100 SUB	Swivel castor with total lock	100x43	300	125	128x102	105x80	11	100		142,80
88-100 SUB	Fixed castor	100x43	300	125	122x77	100x48	11			99,72
61-125 SUB	Swivel castor	125x35	325	156	162x133	140x105	11	100		197,40
61-150 SUB	Swivel castor	150x45	540	181	162x133	140x105	11	119		255,60
88-150 SUB	Fixed castor	150x45	540	195	165x110	137x74	11			190,08