

Heavy Duty Series GT, Wheel SU

 max 1100 kg  -30 °C - +80 °C  100-250 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: Cast polyurethane, 95±3 Shore A
Wheel centre, Cast-iron - painted

Material Fork



Non-Kingpin swivel head with hardened steel raceways and hardened steel balls, forged and tempered, fitted with grease nipple, wheel axle bolted and locked

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Heavy duty dollies
- Machinery moving dollies
- Scaffolds

 ROLLENBAU



SWIVEL CASTOR



WHEEL BRAKE



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
GT 100 SUB	Swivel castor	100x43	300	140	138x110	105x80	10	104		317,76
GTF 100 SUB	Fixed castor	100x43	300	140	138x110	105x80	10			161,88
GT 150 SUB	Swivel castor	150x45	725	200	150x105	105x80	13	150		308,28
GTBR 150 SUB	Swivel castor with wheel brake	150x45	725	200	150x105	105x80	13	150		373,56
GTF 150 SUB	Fixed castor	150x45	725	200	150x105	105x80	13			197,52
GT 200 SUB	Swivel castor	200x51	1000	250	150x105	105x80	13	187		347,76
GTBR 200 SUB	Swivel castor with wheel brake	200x51	1000	250	150x105	105x80	13	187		406,56
GT 250 SUB	Swivel castor	250x51	1100	300	150x105	105x80	13	190		480,96
GTF 250 SUB	Fixed castor	250x51	1100	300	150x105	105x80	13			369,36