

Heavy Duty Series PD, Wheel ZS

 max 850 kg  -30 °C - +80 °C  100-250 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: cast-polyurethane 85 +- 3 shore A soft
Wheel center: Cast-iron wheel centre - painted



Advantages

- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Heavy duty dollies
- Machinery moving dollies
- Scaffolds
- Racks

 ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
PD 101 ZSK	Swivel castor	100x40	240	138	105x85	80x60	8,5	94		103,80
PDT 101 ZSK	Swivel castor with total lock	100x40	240	138	105x85	80x60	8,5	140		125,40
PDF 101 ZSK	Fixed castor	100x40	240	138	105x85	80x60	8,5			81,00
PD 126 ZSK	Swivel castor	125x40	280	164	135x110	105x80	10,5	106		121,08
PDT 126 ZSK	Swivel castor with total lock	125x40	280	164	135x110	105x80	10,5	140		142,68
PDF 126 ZSK	Fixed castor	125x40	280	164	135x110	105x80	10,5			99,24
PD 150 ZSK	Swivel castor	150x40	400	195	135x110	105x80	10,5	127		132,24
PDT 150 ZSK	Swivel castor with total lock	150x40	400	195	135x110	105x80	10,5	140		149,64
PDF 150 ZSK	Fixed castor	150x40	400	195	135x110	105x80	10,5			110,04
PD 200 ZSK	Swivel castor	200x50	800	250	135x110	105x80	12,5	167		201,84
PDT 200 ZSK	Swivel castor with total lock	200x50	800	250	135x110	105x80	12,5	170		242,28
PDF 200 ZSK	Fixed castor	200x50	800	250	135x110	105x80	12,5			167,28
PD 250 ZSK	Swivel castor	250x50	850	305	135x110	105x80	12,5	198		272,16
PDT 250 ZSK	Swivel castor with total lock	250x50	850	305	135x110	105x80	12,5	198		311,88
PDF 250 ZSK	Fixed castor	250x50	850	305	135x110	105x80	12,5			248,28