

Heavy Duty Series PD, Wheel TLS

 max 700 kg  -20 °C - +80 °C  125-200 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: cast polyurethane, 70±3 Shore A
Core: Die-cast aluminium alloy

Material Fork



Finish: electro-zinc plated, hardened steel balls, double ball race
– hardened steel sheet, with strong Kingpin bolted and locked –
adjustable, thermoplastic dust protection ring and seal, wheel axle
bolted, adjustable total lock – leading or trailing available

Advantages

- ✓ very silent in motion
- ✓ low rolling resistance
- ✓ high abrasion and tear resistance
- ✓ high resistance to shocks
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Metal-Technology
- Heavy duty dollies
- Machinery moving dollies
- Scaffolds
- Workshops
- Racks
- Building-Industry
- Carpentry

 ROLLENBAU



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
PS 125 TLSK	Swivel castor	125x50	700	172	135x110	105x80	10,5	107		105,96
PST 125 TLSK	Swivel castor with total lock	125x50	700	172	135x110	105x80	10,5	140		129,36
PSF 125 TLSK	Fixed castor	125x50	700	172	135x110	105x80	10,5			82,20
PS 150 TLSK	Swivel castor	150x50	700	203	135x110	105x80	12,5	140		126,12
PST 150 TLSK	Swivel castor with total lock	150x50	700	203	135x110	105x80	12,5	170		150,00
PSF 150 TLSK	Fixed castor	150x50	700	203	135x110	105x80	12,5			100,32
PD 200 TLSK	Swivel castor	200x50	700	250	135x110	105x80	12,5	167		183,84
PDT 200 TLSK	Swivel castor with total lock	200x50	700	250	135x110	105x80	12,5	170		228,24
PDF 200 TLSK	Fixed castor	200x50	700	250	135x110	105x80	12,5			194,76