


Hospital Castor Series 390, Wheel G



max 110 kg -20 °C - +60 °C 125-150 mm



Material



Solid rubber tyre blue-grey, 80 Shore A
Core: steel rim and metal thread guard, zinc passivated cone bearing

Material Fork



Finish: zinc passivated or chrome-plated, protected from dust and water ingress by plastic sealing ring or with highquality plastic cover (white RAL 9010 or metallic) suitable for disinfecting cubicle, double ball bearing in swivel head series, integrated selection mechanism with total lock or directional and total lock, continually greased

Advantages

- ✓ free of contact discoloration
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Hospital beds



WITH TOTAL OR TOTAL AND DIRECTIONAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	TRANSVERSE BORE MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
390 S 127 GK	Swivel castor with total lock	125x32	100	158	27,8	M8x19	106,5		auf Anfrage
390 SR 127 GK	SWIVEL CASTOR with total and directional Lock	125x32	100	158	27,8	M8x19	106,5		auf Anfrage
390 S 150 GK	Swivel castor with total lock	150x32	110	184	27,8	M8x19	126		auf Anfrage
390 SR 150 GK	SWIVEL CASTOR with total and directional Lock	150x32	110	184	27,8	M8x19	126		auf Anfrage