

Hospital Castor Series 391, Wheel EL



 max 120 kg  -20 °C - +80 °C  125-150 mm

 **swivels easily**

 **wear resistant**

 **shock proof**

 **floor protective**

 **weather proof**

Material



Thermoplastic polyurethane tyre iron grey RAL 7011, 95 Shore A**, electrically conductive, NON-MARKING
Core: Plastic wheel centre and thread guard, silver grey RAL 7001, precision ball bearing

Material Fork



Finish: zinc passivated or chrome-plated, protected from dust and water ingress by plastic sealing ring or with highquality plastic cover (white RAL 9010 or metallic) suitable for disinfecting cubicle, precision ball bearing in swivel head, integrated selection mechanism with total lock or directional and total lock, continually greased



WITH TOTAL OR TOTAL AND DIRECTIONAL LOCK

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ low rolling resistance
- ✓ non-marking
- ✓ high resistance to shocks
- ✓ good chemical resistance

Applications

- Hospital beds

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	TRANSVERSE BORE MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
391 S 127 EL	Swivel castor with total lock	125x32	100	164	27,8	M8x19	106,5		auf Anfrage
391 SR 127 EL	SWIVEL CASTOR with total and directional Lock	125x32	100	164	27,8	M8x19	106,5		auf Anfrage
391 S 150 EL	Swivel castor with total lock	150x32	120	191	27,8	M8x19	126		auf Anfrage
391 SR 150 EL	SWIVEL CASTOR with total and directional Lock	150x32	120	191	27,8	M8x19	126		auf Anfrage