


Hospital Castor Series 391, Wheel ELS



max 110 kg -20 °C - +60 °C 125-150 mm



WITH TOTAL OR TOTAL AND DIRECTIONAL
LOCK

Material



Solid rubber tyre black, 80 Shore A electrically conductive
Core: Steel rim and metal thread guard, zinc passivated cone bearing

Material Fork



Finish: zinc passivated or chrome-plated, protected from dust and water ingress by plastic sealing ring or with highquality plastic cover (white RAL 9010 or metallic) suitable for disinfecting cubicle, precision ball bearing in swivel head, integrated selection mechanism with total lock or directional and total lock, continually greased

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ high running performance
- ✓ free of contact discolouration
- ✓ resistant to diluted acids

Applications

- Hospital beds

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	TRANSVERSE BORE MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
391 S 127 ELS	Swivel castor with total lock	125x32	100	164	27,8	M8x19	106,5		auf Anfrage
391 SR 127 ELS	SWIVEL CASTOR with total and directional Lock	125x32	100	164	27,8	M8x19	106,5		auf Anfrage
391 S 150 ELS	Swivel castor with total lock	150x32	110	191	27,8	M8x19	126		101,76
391 SR 150 ELS	SWIVEL CASTOR with total and directional Lock	150x32	110	191	27,8	M8x19	126		105,60