

Institutional Series 315P, Wheel TP



max 60 kg -20 °C - +60 °C 50-75 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Tread: Thermoplastic elastomer coating 95±3 Shore A**
High quality nylon wheel centre

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 46 mm, revited,
dust protection ring, wheel axle bolted and locked, wheel-/ total
lock – spring stainless steel

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Portable bar units
- Metal-Technology
- Workshops
- Book carts
- Sidetables
- Laboratory equipment
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
315 PT 50 TPK	Swivel castor	50x18	40	73	58x58	40x40/42x42	6,2	51		16,80
316 PT 50 TPK	Swivel castor with total lock	50x18	40	73	58x58	40x40/42x42	6,2	73		22,20
670 PT 50 TPK	Fixed castor	50x18	40	73	58x58	40x40/42x42	6,2			12,84
315 PT 50 V	Swivel castor	50x18	40	73	58x58	40x40/42x42	6,2	51		18,00
316 PT 50 V	Swivel castor with total lock	50x18	40	73	58x58	40x40/42x42	6,2	73		24,00
670 PT 50 V	Fixed castor	50x18	40	73	58x58	40x40/42x42	6,2			16,32
315 PT 75 DEK	Swivel castor	75x25	60	97	58x58	40x40/42x42	6,2	68		28,44
316 PT 75 DEK	Swivel castor with total lock	75x25	60	97	58x58	40x40/42x42	6,2	83		34,20
670 PT 75 DEK	Fixed castor	75x25	60	97	58x58	40x40/42x42	6,2			25,56
315 PT 75 TPK	Swivel castor	75x25	60	97	58x58	40x40/42x42	6,2	68		58,92
316 PT 75 TPK	Swivel castor with total lock	75x25	60	97	58x58	40x40/42x42	6,2	83		64,80
670 PT 75 TPK	Fixed castor	75x25	60	97	58x58	40x40/42x42	6,2			56,04