

Institutional Series 315P, Wheel G



max 70 kg -20 °C - +60 °C 50-100 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Standard rubber tyre grey
Nylon rim

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 46 mm, revited,
dust protection ring, wheel axle bolted and locked, wheel-/ total
lock – spring stainless steel

Advantages

- ✓ non-marking - floor protective
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Portable bar units
- Metal-Technology
- Workshops
- Book carts
- Sidetables
- Laboratory equipment
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
315 PT 50 G	Swivel castor	50x18	40	73	58x58	40x40/42x42	6,2	51	☐	15,12
316 PT 50 G	Swivel castor with total lock	50x18	40	73	58x58	40x40/42x42	6,2	73	☐	21,24
670 PT 50 G	Fixed castor	50x18	40	73	58x58	40x40/42x42	6,2		☐	13,08
315 PT 50 GL	Swivel castor	50x18	40	73	58x58	40x40/42x42	6,2	51	☐	12,72
316 PT 50 GL	Swivel castor with total lock	50x18	40	73	58x58	40x40/42x42	6,2	73	☐	18,00
670 PT 50 GL	Fixed castor	50x18	40	73	58x58	40x40/42x42	6,2		☐	9,96
315 PT 75 GK	Swivel castor	75x25	60	97	58x58	40x40/42x42	6,2	68	☐	20,88
316 PT 75 GK	Swivel castor with total lock	75x25	60	97	58x58	40x40/42x42	6,2	83	☐	27,24
670 PT 75 GK	Fixed castor	75x25	60	97	58x58	40x40/42x42	6,2		☐	18,00
315 PT 75 GKL	Swivel castor	75x25	60	97	58x58	40x40/42x42	6,2	68	☐	17,40
316 PT 75 GKL	Swivel castor with total lock	75x25	60	97	58x58	40x40/42x42	6,2	83	☐	23,52
670 PT 75 GKL	Fixed castor	75x25	60	97	58x58	40x40/42x42	6,2		☐	14,64
315 PT 75 G	Swivel castor	75x22	60	97	58x58	40x40/42x42	6,2	68	☐	17,16
316 PT 75 G	Swivel castor with total lock	75x22	60	97	58x58	40x40/42x42	6,2	83	☐	22,56
670 PT 75 G	Fixed castor	75x22	60	97	58x58	40x40/42x42	6,2		☐	14,16
315 PT 75 GL	Swivel castor	75x22	60	97	58x58	40x40/42x42	6,2	68	☐	14,64
316 PT 75 GL	Swivel castor with total lock	75x22	60	97	58x58	40x40/42x42	6,2	83	☐	19,80
670 PT 75 GL	Fixed castor	75x22	60	97	58x58	40x40/42x42	6,2		☐	10,08
315 PT 100 GK	Swivel castor	100x24	70	121	58x58	40x40/42x42	6,2	85	☐	30,48
316 PT 100 GK	Swivel castor with total lock	100x24	70	121	58x58	40x40/42x42	6,2	96	☐	34,68
670 PT 100 GK	Fixed castor	100x24	70	121	58x58	40x40/42x42	6,2		☐	31,32
315 PT 100 GKL	Swivel castor	100x24	70	121	58x58	40x40/42x42	6,2	85	☐	23,52
316 PT 100 GKL	Swivel castor with total lock	100x24	70	121	58x58	40x40/42x42	6,2	96	☐	28,20
670 PT 100 GKL	Fixed castor	100x24	70	121	58x58	40x40/42x42	6,2		☐	21,60
315 PT 100 GL	Swivel castor	100x25	70	121	58x58	40x40/42x42	6,2	85	☐	20,52

316 PT 100 GL	Swivel castor with total lock	100x25	70	121	58x58	40x40/42x42	6,2	96	==	25,56
670 PT 100 GL	Fixed castor	100x25	70	121	58x58	40x40/42x42	6,2		==	22,56