

Institutional Series 315P, Wheel EL ⚡

ROLLENBAU

max 70 kg $-20^{\circ}\text{C} - +60^{\circ}\text{C}$ 50-100 mm

+++
swivels easily

+++
wear resistant

++
shock proof

++
floor protective

+++
weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– $\varnothing 46$ mm, revited,
dust protection ring, wheel axle bolted and locked, wheel-/ total
lock – spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Portable bar units
- Metal-Technology
- Workshops
- Book carts
- Sidetables
- Laboratory equipment
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



FIXED CASTOR

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
315 PT 50 EL	Swivel castor	50x18	40	73	58x58	40x40/42x42	6,2	51		20,04
316 PT 50 EL	Swivel castor with total lock	50x18	40	73	58x58	40x40/42x42	6,2	73		25,44
670 PT 50 EL	Fixed castor	50x18	40	73	58x58	40x40/42x42	6,2			17,28
315 PT 75 EL	Swivel castor	75x25	60	97	58x58	40x40/42x42	6,2	68		28,20
316 PT 75 EL	Swivel castor with total lock	75x25	60	97	58x58	40x40/42x42	6,2	83		34,20
670 PT 75 EL	Fixed castor	75x25	60	97	58x58	40x40/42x42	6,2			25,44
315 PT 100 EL	Swivel castor	100x24	70	121	58x58	40x40/42x42	6,2	85		36,72
316 PT 100 EL	Swivel castor with total lock	100x24	70	121	58x58	40x40/42x42	6,2	95		40,80
670 PT 100 EL	Fixed castor	100x24	70	121	58x58	40x40/42x42	6,2			34,68