

Institutional Series 315R, Wheel G



max 70 kg -20 °C - +60 °C 50-100 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Standard rubber tyre grey
Nylon rim

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 46 mm, revited,
dust protection ring, wheel axle bolted and locked, wheel-/ total
lock – spring stainless steel

Advantages

- ✓ non-marking - floor protective
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Portable bar units
- Metal-Technology
- House keeping carts
- Workshops
- Book carts
- Sidetables
- Laboratory equipment
- Instrument stands
- School furniture
- Bedside carts
- Hanging racks
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
315 RÜ10 50 G	Swivel castor	50x18	40	70	10,5	51	==	12,36
316 RÜ10 50 G	Swivel castor with total lock	50x18	40	70	10,5	73	==	17,40
315 RÜ12 50 G	Swivel castor	50x18	40	70	12,5	51	==	12,36
316 RÜ12 50 G	Swivel castor with total lock	50x18	40	70	12,5	73	==	17,40
315 RÜ10 50 GL	Swivel castor	50x18	40	70	10,5	51	==	10,08
316 RÜ10 50 GL	Swivel castor with total lock	50x18	40	70	10,5	73	==	13,08
315 RÜ12 50 GL	Swivel castor	50x18	40	70	12,5	51	==	10,08
316 RÜ12 50 GL	Swivel castor with total lock	50x18	40	70	12,5	73	==	13,08
315 RÜ10 75 GK	Swivel castor	75x25	60	97	10,5	68	⊖	19,32
316 RÜ10 75 GK	Swivel castor with total lock	75x25	60	97	10,5	83	⊖	24,84
315 RÜ12 75 GK	Swivel castor	75x25	60	97	12,5	68	⊖	19,44
316 RÜ12 75 GK	Swivel castor with total lock	75x25	60	97	12,5	83	⊖	24,96
315 RÜ10 75 GKL	Swivel castor	75x25	60	97	10,5	68	⊖	16,80
316 RÜ10 75 GKL	Swivel castor with total lock	75x25	60	97	10,5	83	⊖	21,60
315 RÜ12 75 GKL	Swivel castor	75x25	60	97	12,5	68	⊖	16,80
316 RÜ12 75 GKL	Swivel castor with total lock	75x25	60	97	12,5	83	⊖	21,60
315 RÜ10 75 G	Swivel castor	75x22	60	97	10,5	68	==	14,88
316 RÜ10 75 G	Swivel castor with total lock	75x22	60	97	10,5	83	==	21,24
315 RÜ12 75 G	Swivel castor	75x22	60	97	12,5	68	==	14,88
316 RÜ12 75 G	Swivel castor with total lock	75x22	60	97	12,5	83	==	21,24
315 RÜ10 75 GL	Swivel castor	75x22	60	97	10,5	68	==	12,36
316 RÜ10 75 GL	Swivel castor with total lock	75x22	60	97	10,5	83	==	17,40
315 RÜ12 75 GL	Swivel castor	75x22	60	97	12,5	68	==	12,36
316 RÜ12 75 GL	Swivel castor with total lock	75x22	60	97	12,5	83	==	17,40
315 RÜ10 100 GK	Swivel castor	100x24	70	121	10,5	85	⊖	28,44
316 RÜ10 100 GK	Swivel castor with total lock	100x24	70	121	10,5	96	⊖	33,24
315 RÜ12 100 GK	Swivel castor	100x24	70	121	12,5	85	⊖	28,44
316 RÜ12 100 GK	Swivel castor with total lock	100x24	70	121	12,5	96	⊖	33,24
315 RÜ10 100 GKL	Swivel castor	100x24	70	121	10,5	85	⊖	21,96
316 RÜ10 100 GKL	Swivel castor with total lock	100x24	70	121	10,5	96	⊖	27,24
315 RÜ12 100 GKL	Swivel castor	100x24	70	121	12,5	85	⊖	21,96

316 RÜ12 100 GKL	Swivel castor with total lock	100x24	70	121	12,5	96		27,24
315 RÜ10 100 GL	Swivel castor	100x25	70	121	10,5	85		18,84
316 RÜ10 100 GL	Swivel castor with total lock	100x25	70	121	10,5	96		24,00
315 RÜ12 100 GL	Swivel castor	100x25	70	121	12,5	85		18,84
316 RÜ12 100 GL	Swivel castor with total lock	100x25	70	121	12,5	96		24,00