

Institutional Series 315R, Wheel EL ⚡

ROLLENBAU

max 70 kg  -20 °C - +60 °C  50-100 mm

+++
swivels easily

+++
wear resistant

++
shock proof

++
floor protective

+++
weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 46 mm, revited,
dust protection ring, wheel axle bolted and locked, wheel-/ total
lock – spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Portable bar units
- Metal-Technology
- Workshops
- Book carts
- Sidetables
- Laboratory equipment
- Instrument stands
- School furniture
- Bedside carts
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
315 RÜ10 50 EL	Swivel castor	50x18	40	70	10,5	51		18,36
316 RÜ10 50 EL	Swivel castor with total lock	50x18	40	70	10,5	73		23,52
315 RÜ12 50 EL	Swivel castor	50x18	40	70	12,5	51		18,60
316 RÜ12 50 EL	Swivel castor with total lock	50x18	40	70	12,5	73		23,52
315 RÜ10 75 EL	Swivel castor	75x25	60	97	10,5	68		27,00
316 RÜ10 75 EL	Swivel castor with total lock	75x25	60	97	10,5	83		32,64
315 RÜ12 75 EL	Swivel castor	75x25	60	97	12,5	68		27,00
316 RÜ12 75 EL	Swivel castor with total lock	75x25	60	97	12,5	83		32,64
315 RÜ10 100 EL	Swivel castor	100x24	70	121	10,5	85		35,40
316 RÜ10 100 EL	Swivel castor with total lock	100x24	70	121	10,5	96		39,96
315 RÜ12 100 EL	Swivel castor	100x24	70	121	12,5	85		35,40
316 RÜ12 100 EL	Swivel castor with total lock	100x24	70	121	12,5	96		39,96