

Institutional Series 320P, Wheel TP



max 90 kg -20 °C - +60 °C 50-75 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Tread: Thermoplastic elastomer coating 95±3 Shore A**
High quality nylon wheel centre

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing, revited, wheel axle bolted and locked, wheel-/total lock – spring stainless steel

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Portable bar units
- Metal-Technology
- Kitchen equipment
- Workshops
- Book carts
- Laboratory equipment
- Room service carts
- Instrument stands
- Diagnostic equipment
- School furniture
- Automobile test equipment
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
320 PT 50 TPK	Swivel castor	50x18+18	60	70	58x58	40x40/42x42	6,2	53		29,64
321 PT 50 TPK	Swivel castor with wheel brake	50x18+18	60	70	58x58	40x40/42x42	6,2	78		35,64
320 PT 50 V	Swivel castor	50x18+18	60	70	58x58	40x40/42x42	6,2	53		27,36
321 PT 50 V	Swivel castor with wheel brake	50x18+18	60	70	58x58	40x40/42x42	6,2	78		33,48
320 PT 75 DK	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69		52,68
321 PT 75 DK	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106		71,88
320 PT 75 TPK	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69		82,92
321 PT 75 TPK	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106		102,36