

Institutional Series 320P, Wheel G



max 90 kg -20 °C - +60 °C 50-75 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Standard rubber tyre grey
Nylon rim

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing, revited, wheel axle bolted and locked, wheel-/total lock – spring stainless steel

Advantages

- ✓ non-marking - floor protective
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Portable bar units
- Metal-Technology
- Kitchen equipment
- Workshops
- Book carts
- Laboratory equipment
- Room service carts
- Instrument stands
- Diagnostic equipment
- School furniture
- Automobile test equipment
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICLE TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
320 PT 50 G	Swivel castor	50x18+18	60	70	58x58	40x40/42x42	6,2	53	≡	20,88
321 PT 50 G	Swivel castor with wheel brake	50x18+18	60	70	58x58	40x40/42x42	6,2	78	≡	27,24
320 PT 50 GL	Swivel castor	50x18+18	60	70	58x58	40x40/42x42	6,2	53	≡	16,92
321 PT 50 GL	Swivel castor with wheel brake	50x18+18	60	70	58x58	40x40/42x42	6,2	78	≡	21,48
320 PT 75 GK	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69	⊙	38,64
321 PT 75 GK	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106	⊙	59,28
320 PT 75 GKL	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69	⊙	34,20
321 PT 75 GKL	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106	⊙	54,60
320 PT 75 G	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69	≡	32,64
321 PT 75 G	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106	≡	53,16
320 PT 75 GL	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69	≡	28,08
321 PT 75 GL	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106	≡	48,72