

Institutional Series 320P, Wheel EL ⚡

ROLLENBAU

max 90 kg  -20 °C - +60 °C  50-75 mm

+++
swivels easily

+++
wear resistant

++
shock proof

++
floor protective

++
weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball
bearing, revited, wheel axle bolted and locked, wheel-/total lock –
spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Portable bar units
- Metal-Technology
- Workshops
- Book carts
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
320 PT 50 EL	Swivel castor	50x18+18	60	70	58x58	40x40/42x42	6,2	53		29,76
321 PT 50 EL	Swivel castor with wheel brake	50x18+18	60	70	58x58	40x40/42x42	6,2	78		36,36
320 PT 75 EL	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69		50,64
321 PT 75 EL	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106		69,96