

Institutional Series 320P, Wheel P



max 90 kg -30 °C - +70 °C 50-75 mm

swivels easily	wear resistant	shock proof
floor protective	weather proof	

Material



Casted high quality nylon wheel

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing, revited, wheel axle bolted and locked, wheel-/total lock – spring stainless steel

Advantages

- ✓ easy running on smooth floors
- ✓ impact proof
- ✓ high abrasion resistance
- ✓ easy to clean
- ✓ high chemical resistance

Applications

- Portable bar units
- Metal-Technology
- Workshops
- Book carts
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
320 PT 50 P	Swivel castor	50x18+18	60	70	58x58	40x40/42x42	6,2	53	==	14,28
321 PT 50 P	Swivel castor with wheel brake	50x18+18	60	70	58x58	40x40/42x42	6,2	78	==	21,48
320 PT 75 P	Swivel castor	75x25+25	90	103	77x67	61,5x51,5	8,5	69	==	31,32
321 PT 75 P	Swivel castor with total lock	75x25+25	90	103	77x67	61,5x51,5	8,5	106	==	51,72