

Institutional Series 320R, Wheel EL ⚡

ROLLENBAU

max 90 kg $-20^{\circ}\text{C} - +60^{\circ}\text{C}$ 50-75 mm

+++
swivels easily

+++
wear resistant

++
shock proof

+++
floor protective

+++
weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball
bearing, revited, wheel axle bolted and locked, wheel-/total lock –
spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Portable bar units
- Metal-Technology
- Workshops
- Book carts
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH WHEEL BRAKE

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
320 RÜ 50 EL	Swivel castor	50x18+18	55	70	10,5	53		28,56
321 RÜ 50 EL	Swivel castor with wheel brake	50x18+18	55	70	10,5	78		34,44
320 RÜ 75 EL	Swivel castor	75x25+25	90	100	10,5	69		47,64
321 RÜ 75 EL	Swivel castor with total lock	75x25+25	90	100	10,5	106		66,12