

Institutional Series 330LP, Wheel TP



max 100 kg -20 °C - +60 °C 125-125 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: Thermoplastic elastomer coating 95±3 Shore A**
High quality nylon wheel centre

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, revited, dust protection ring, wheel axle bolted and
locked, total lock – spring stainless steel

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Metal-Technology
- Kitchen equipment
- Mail carts
- Workshops
- Laboratory equipment
- Trolleys
- Room service carts
- Instrument stands
- School furniture
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330L PT 127 TPKX	Swivel castor	125x32	100	158	90x70	75x45/62x52	8,5	103		66,12
331L PT 127 TPKX	Swivel castor with total lock	125x32	100	158	90x70	75x45/62x52	8,5	130		82,20