

Institutional Series 330LP, Wheel G



max 100 kg -20 °C - +60 °C 125-125 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Standard rubber tyre grey
Nylon rim

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, revited, dust protection ring, wheel axle bolted and
locked, total lock – spring stainless steel

Advantages

- ✓ non-marking - floor protective
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Metal-Technology
- Kitchen equipment
- Mail carts
- Workshops
- Laboratory equipment
- Trolleys
- Room service carts
- Instrument stands
- School furniture
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330L PT 127 GK	Swivel castor	125x32	100	161	90x70	75x45/62x52	8,5	103		40,44
331L PT 127 GK	Swivel castor with total lock	125x32	100	161	90x70	75x45/62x52	8,5	130		57,96
330L PT 127 GKL	Swivel castor	125x32	100	161	90x70	75x45/62x52	8,5	103		28,20
331L PT 127 GKL	Swivel castor with total lock	125x32	100	161	90x70	75x45/62x52	8,5	130		45,12
330L PT 127 GL	Swivel castor	125x32	100	161	90x70	75x45/62x52	8,5	103		24,36
331L PT 127 GL	Swivel castor with total lock	125x32	100	161	90x70	75x45/62x52	8,5	130		40,68