

Institutional Series 330LP, Wheel EL

 ROLLENBAU

 max 100 kg  -20 °C - +60 °C  125-125 mm

 swivels easily

 wear resistant

 shock proof

 floor protective

 weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, revited, dust protection ring, wheel axle bolted and
locked, total lock – spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Metal-Technology
- Kitchen equipment
- Mail carts
- Workshops
- Laboratory equipment
- Trolleys
- Room service carts
- Instrument stands
- School furniture
- Carpentry



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	DIMENSION OF TOP PLATE TP MM	HOLE SPACING HS MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330L PT 127 EL	Swivel castor	125x32	100	158	90x70	75x45/62x52	8,5	103		51,96
331L PT 127 EL	Swivel castor with total lock	125x32	100	158	90x70	75x45/62x52	8,5	130		67,68