

Institutional Series 330LR, Wheel G



max 100 kg -20 °C - +60 °C 125-125 mm

swivels easily

wear resistant

shock proof

floor protective

weather proof

Material



Standard rubber tyre grey
Nylon rim

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, revited, dust protection ring, wheel axle bolted and
locked, total lock – spring stainless steel

Advantages

- ✓ non-marking - floor protective
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Metal-Technology
- Laundry trucks
- Kitchen equipment
- Workshops
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICLE TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330L RÜ10 127 GK	Swivel castor	125x32	100	158	10,5	103		38,64
331L RÜ10 127 GK	Swivel castor with total lock	125x32	100	158	10,5	130		56,04
330L RÜ12 127 GK	Swivel castor	125x32	100	158	12,5	103		38,64
331L RÜ12 127 GK	Swivel castor with total lock	125x32	100	158	12,5	130		56,04
330L RÜ10 127 GKL	Swivel castor	125x32	100	158	10,5	103		25,56
331L RÜ10 127 GKL	Swivel castor with total lock	125x32	100	158	10,5	130		43,92
330L RÜ12 127 GKL	Swivel castor	125x32	100	158	12,5	103		25,56
331L RÜ12 127 GKL	Swivel castor with total lock	125x32	100	158	12,5	130		43,92
330L RÜ10 127 GL	Swivel castor	125x32	100	158	10,5	103		27,00
331L RÜ10 127 GL	Swivel castor with total lock	125x32	100	158	10,5	130		38,88
330L RÜ12 127 GL	Swivel castor	125x32	100	158	12,5	103		27,00
331L RÜ12 127 GL	Swivel castor with total lock	125x32	100	158	12,5	130		66,00