

Institutional Series 330LR, Wheel EL

 ROLLENBAU

 max 100 kg  -20 °C - +60 °C  125-125 mm

 swivels easily

 wear resistant

 shock proof

 floor protective

 weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4\Omega$
nylon rim, conductive, volume resistance value $<10^4\Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, revited, dust protection ring, wheel axle bolted and
locked, total lock – spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Metal-Technology
- Kitchen equipment
- Workshops
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	HOLE-Ø HD MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330L RÜ10 127 EL	Swivel castor	125x32	100	158	10,5	103		50,40
331L RÜ10 127 EL	Swivel castor with total lock	125x32	100	158	10,5	130		66,00
330L RÜ12 127 EL	Swivel castor	125x32	100	158	12,5	103		50,40
331L RÜ12 127 EL	Swivel castor with total lock	125x32	100	158	12,5	130		66,00