

Institutional Series 330LZ, Wheel EL

 ROLLENBAU

 max 100 kg  -20 °C - +60 °C  125-125 mm

 swivels easily

 wear resistant

 shock proof

 floor protective

 weather proof

Material



rubber tyre, electrically
conductive, volume resistance value $<10^4 \Omega$
nylon rim, conductive, volume resistance value $<10^4 \Omega$

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, stem revited, wheel axle bolted and locked, total/
directional lock – spring stainless steel

Advantages

- ✓ electrically conductive
- ✓ silent in motion
- ✓ good running performance
- ✓ resistant to diluted acids

Applications

- Metal-Technology
- Kitchen equipment
- Workshops
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



WITH DIRECTIONAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	TRANSVERSE BORE MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330L Z18 127 EL	Swivel castor	125x32	100	161	18x62	M6 auf 30	103		45,12
331L Z18 127 EL	Swivel castor with total lock	125x32	100	161	18x62	M6 auf 19	130		73,92