

Institutional Series 330Z, Wheel TP



max 110 kg -20 °C - +60 °C 125-150 mm

+++
swivels easily

+++
wear resistant

+++
shock proof

+++
floor protective

+++
weather proof

Material



Tread: Thermoplastic elastomer coating 95±3 Shore A**
High quality nylon wheel centre

Material Fork



Finish: zinc plated and chromate coated, large double ball bearing
– Ø 57 mm, stem revited, wheel axle bolted and locked, total-/
directional lock – spring stainless steel

Advantages

- ✓ silent in motion
- ✓ low rolling resistance
- ✓ high resistance to shocks
- ✓ non-marking
- ✓ easy to clean
- ✓ good chemical resistance

Applications

- Metal-Technology
- Kitchen equipment
- Food & dish carts
- Food service carts
- Food & dish carts
- Food service carts
- Workshops
- Laboratory equipment
- Room service carts
- Instrument stands
- School furniture
- Carpentry
- Health-Professionals



SWIVEL CASTOR



SWIVEL CASTOR WITH TOTAL LOCK



WITH DIRECTIONAL LOCK

Dimensions

ARTICLE NUMBER	ARTICEL TYPE	WHEEL-Ø A X WIDTH B MM	LOAD CAPACITY KG	OVERALL HEIGHT H MM	STERN MM	TRANSVERSE BORE MM	SWIVEL RADIUS SR MM	WHEEL BEARING	PRICE €
330 Z18 127 TPK	Swivel castor	125x32	100	158	18x62	M8 auf 30	104		50,40
331 Z18 127 TPK	Swivel castor with total lock	125x32	100	158	18x62	M8 auf 30	130		69,24
337 Z18 127 TPK	Swivel castor with directional lock	125x32	100	158	18x62	M8 auf 30	130		120,24
330 Z18 127 TP	Swivel castor	125x32	100	158	18x62	M8 auf 30	104		42,60
331 Z18 127 TP	Swivel castor with total lock	125x32	100	158	18x62	M8 auf 30	130		60,48
337 Z18 127 TP	Swivel castor with directional lock	125x32	100	158	18x62	M8 auf 30	130		99,60
330 Z18 150 TPK	Swivel castor	150x32	110	187	18x62	M8 auf 30	121		96,36
331 Z18 150 TPK	Swivel castor with total lock	150x32	110	187	18x62	M8 auf 30	121		128,64
337 Z18 150 TPK	Swivel castor with directional lock	150x32	110	187	18x62	M8 auf 30	121		122,16